

Bosch Heat Pump IDS 2.0

Inverter Ducted Split System 2.0

Everything you loved about IDS 1.0 but now even better with all AHRI certified BOVA2.0 + BVA2.0 combinations meeting ENERGY STAR requirements and offering enhanced humidity control features. Choose the best, choose Bosch!

BOSCH





www.BoschHeatingAndCooling.com

Maximum Comfort, Minimum Energy!

Bosch Inverter Ducted Split System IDS 2.0

The Bosch Inverter Ducted Split system provides supremely-efficient comfort by adjusting compressor capacity rather than a simple on/off control like other units, thereby reducing operating costs and saving you money. With enhanced humidity control and higher effiency, the performance of the IDS 2.0 system provides you with maximum comfort with minimum energy usage! The system's intelligent features work in tandem with your thermostat to automatically adjust to your preferences, while integrated sound dampening features keep the units nice and quiet for your peace of mind.

Features

- ▶ Premium efficiency Up to 20.5 SEER and 10.5 HSPF
- 10 speed ECM outdoor blower for whisper quiet and efficient operation – as low as 56 dBA⁽¹⁾
- Two stage x13 ECM blower for enhanced humidity control
- Easy to install compatible with most standard 24 VAC heat pump thermostats
- ▶ 10-year Residential Limited Warranty⁽²⁾
- All AHRI certified BOVA2.0 + BVA2.0 combinations meet the requirements for ENERGY STAR
- There are 2,3,4, & 5 ton ENERGY STAR rated systems available when paired with Bosch 96% Furnaces*
- > Aluminum evaporator coil for superior corrosion resistance
- Compatible with the Bosch Connected Control (BCC) Thermostat family^{*}



(1) 56 dBA sound level is based on outdoor unit. (2) Please go to boschheatingandcooling.com for full limited warranty details *Product sold separately

Consistent Room Temperature

Conventional heat pumps frequently cycle on and off, resulting in uncomfortable temperature fluctuations. IDS 2.0 inverter-driven heat pumps are able to self-adjust, providing consistent room temperature, even when the outdoor temperature dips to -4° F.

Consume Only the Energy You Need

Modulating inverter systems deliver only the amount of hot or cool air needed to achieve the desired temperature – no more, no less. With up to 20.5 SEER and 10.5 HSPF, the Inverter Ducted Split system can provide you with maximum comfort levels at a minimum cost.

Fast Response

It takes traditional systems a long time to reach the homeowner's desired temperature, while the boosted compressor speed of inverter systems allows for quicker, smoother and more efficient heating and cooling.

Intelligent Control

The system will adjust the output capacity to match your ideal temperature requirements. Also, with a two speed AHU fan control, the system delivers enhanced humidity control.

Quiet Comfort Achieved

The Bosch Inverter Ducted Split system is one of the quietest air-to-air heat pumps on the market. Through the use of silent blade technology, sound isolating mounts and outdoor condensing section placement - the system can deliver outdoor sound levels as low as 56 dBA - which is far superior to any standard system on the market.

Energy Use is Even and Steady

The frequent on and off of traditional units creates an in-rush current surge which uses more energy and causes unneeded wear and tear on your system. The Bosch inverter system smoothly ramps up operation, avoiding spikes in energy use and protecting the system's life-cycle.

Residential Limited Warranty⁽²⁾

With the residential limited warranty, you receive peace-of-mind knowing you will receive replacement parts protection for up to 10 years. This standard offering covers all components incorporated into the heat pump system at the time of manufacture. All other components or parts that are purchased from Bosch and installed in the field have a 1-year parts warranty.

10 _{Year} Warranty



IDS 2.0 Components Features & Benefits



Bosch IDS 2.0 High-Efficiency Outdoor Condensing Section (BOVA Model)

- Intelligent control features help adjust the output capacity allowing the unit to keep the temperature at your desired level without fluctuation and to keep humidity in check during the summer months. Whether it be the summer or winter, the system keeps your home comfortable and the living conditions to your desired taste.
 - The air coil design provides exceptional heat transfer and low air-resistance for highefficiency operation that can help lower your energy costs.
 - The direct-drive fan blades provide vortex suppression to reduce sound of airflow exiting the condensing section, thereby retaining relatively low noise at high speed - with sound levels as low as 56 dBA.
 - > The high-efficiency variable capacity inverter compressor can adjust output to any level between 25% and 110%, to perfectly cool and heat your home using minimal energy for maximum comfort.
 - > The condensing units come standard with an electronic expansion valve (EEV) to ensure proper refrigerant flow during all conditions in order to optimize the unit's process to the highest efficiency possible.



Bosch IDS 2.0 Robust & Reliable Indoor Air Handler (BVA Model)

- Material Foil faced insulation material on the inner walls В decreases energy loss and eliminates condensation.
 - Cabinets Painted galvanzied steel cabinet is salt spray tested for improved durability and corrosion-resistance.
- D

G

н

- Electric Heat Can accommodate electric heat with no modification to the cabinet for additional heat on-demand when you need it most.
- Two stage ECM motor Indoor blower stages up and down E to provide enhanced comfort, energy savings, and superior humidity control.
- All-Aluminum Coil With excellent heat transfer, efficiency, and humidity removal, the A-coil is more durable and has a lower chance of refrigerant leakage compared to typical copper coils.
 - Control Board Pocket A dedicated slot for the control board protects it from humidity in the airstream and extends its lifetime.
 - Integrated Drain Pan Made from corrosion-resistant composite material, gently sloped to eliminate standing water.
 - Secondary Drain Pan Flexibility for VT or HZ applications.
 - Filter Rack Factory reserved, provides convenience for field installation and serviceability.



The Complete & Highly Efficient Dual Fuel Heating and Cooling System For Your Home



Bosch's IDS 2.0 Unit

The robust Bosch Inverter Ducted Split Air Source Heat Pump system utilizes just the right amount of energy to achieve ultimate comfort and maximum efficiency while keeping sound levels to a minimum.



Bosch's Cased Coil*

The Inverter Ducted Split Evaporator Coil, when paired with a Bosch Furnace and IDS outdoor condensing section, delivers some of the best comfort levels and efficiency on the market today. Bosch offers a complete range of evaporator coils to fit your needs.



Bosch's BGH96 Furnace*

The BGH96 Gas Furnace is Bosch's first condensing furnace. Offering up to 96% efficiency, a two-stage gas valve, and a multi-speed blower, this ENERGY STAR rated furnace offers premium comfort and energy savings.



Bosch's BCC100^{*}

The BCC100 is a sleek, internet-connected thermostat that offers easy all-in-one control for your heating and cooling systems. It can be controlled using the Bosch Connected Control app and is compatible with most 24VAC HVAC equipment on the market.

Bosch IDS 2.0 | Simply Smart

- ▶ 20.5 SEER and 10.5 HSPF
- ENERGY STAR rated
- Fully-modulating inverter drive Sound levels as low as 56 dBA
- 4 Air handlers 2, 3, 4, 5 Ton
- 2 Condensing units 3 and 5 Ton
- Compatible with most 24 VAC thermostats
- All aluminum evaporator coil
- Operates in heating down to -4° F
- Operates in cooling up to 125° F
- Up to 150 ft lineset
- Bosch quality
- 10-year residential limited warranty*

Field Friendly

- Designed for easy installation
- Simple to set up
- Intuitive controls
- Support readily available
- Field installed electric heater kits

System & Technical Information

Cased Coil

Uncased Coil

Bosch IDS 2.0

The robust Bosch Inverter

Ducted Split 2.0 air-source heat pump system utilizes

just the right amount of


energy to achieve ultimate

comfort and maximum

efficiency while keeping

sound levels to


a minimum.




| CASED COIL DIMENSIONS (IN INCHES) | | | | | | | | | |
|--|-------------------------------------|------|------|------|--|--|--|--|--|
| MODEL NUMBER PART NUMBER WIDTH (W) HEIGHT (H) DEPT | | | | | | | | | |
| BMAC2430ANTD | 8733947947 | 14.5 | 20.0 | 21.0 | | | | | |
| BMAC2430BNTD | 8733947948 | 17.5 | 20.0 | 21.0 | | | | | |
| BMAC3036ANTD | 8733947950 | 14.5 | 20.0 | 21.0 | | | | | |
| BMAC3036BNTD | 8733947951 | 17.5 | 20.0 | 21.0 | | | | | |
| BMAC3036CNTD | 8733947952 | 21.0 | 20.0 | 21.0 | | | | | |
| BMAC4248BNTF | 8733947953 | 17.5 | 30.0 | 21.0 | | | | | |
| BMAC4248CNTF | 8733947954 | 21.0 | 30.0 | 21.0 | | | | | |
| BMAC4248DNTF | 8733947955 | 24.5 | 30.0 | 21.0 | | | | | |
| BMAC4860CNTF | 8733947956 | 21.0 | 30.0 | 21.0 | | | | | |
| BMAC4860DNTF | 8733947957 | 24.5 | 30.0 | 21.0 | | | | | |
| UN | UNCASED COIL DIMENSIONS (IN INCHES) | | | | | | | | |

| UNCASED COIL DIMENSIONS (IN INCHES) | | | | | | | | | | |
|-------------------------------------|-----------|------------|-----------|--|--|--|--|--|--|--|
| CORRESPONDING MODEL NUMBER | WIDTH (W) | HEIGHT (H) | DEPTH (D) | | | | | | | |
| BMAC2430ANTD | 13.375 | 15.625 | 20.5 | | | | | | | |
| BMAC2430BNTD | 16.375 | 15.375 | 20.5 | | | | | | | |
| BMAC3036ANTD | 13.375 | 15.625 | 20.5 | | | | | | | |
| BMAC3036BNTD | 16.375 | 15.375 | 20.5 | | | | | | | |
| BMAC3036CNTD | 19.875 | 15.25 | 20.5 | | | | | | | |
| BMAC4248BNTF | 16.375 | 26.88 | 21.0 | | | | | | | |
| BMAC4248CNTF | 19.875 | 26.8 | 21.0 | | | | | | | |
| BMAC4248DNTF | 23.625 | 26.6 | 21.0 | | | | | | | |
| BMAC4860CNTF | 19.875 | 27.0 | 21.0 | | | | | | | |
| BMAC4860DNTF | 23.625 | 26.8 | 21.0 | | | | | | | |

Air Handler



Condensing Section



| AIR HANDLER 2.0 DIMENSIONS (IN INCHES) | | | | | | | | | |
|---|-------------|-----------|------------|-----------|--|--|--|--|--|
| MODEL SIZE | PART NUMBER | WIDTH (W) | HEIGHT (H) | DEPTH (D) | | | | | |
| 024 | 8733952439 | 19.625 | 46.5 | 21.625 | | | | | |
| 036 | 8733952440 | 19.625 | 46.5 | 21.625 | | | | | |
| 048 | 8733952441 | 22.0 | 54.5 | 24.0 | | | | | |
| 060 | 8733952442 | 22.0 | 54.5 | 24.0 | | | | | |
| CONDENSING SECTION 2.0 DIMENSIONS (IN INCHES) | | | | | | | | | |
| MODEL SIZE | PART NUMBER | WIDTH (W) | HEIGHT (H) | DEPTH (D) | | | | | |
| 036 | 8733952437 | 29.125 | 24.9375 | 29.125 | | | | | |
| 060 | 8733952438 | 29.125 | 33.1875 | 29.125 | | | | | |

| BOSCH BOVA MODEL OUTDOOR UNIT | | | | FIELD | INSTALLED ELEC | TRIC HEAT KITS |
|-------------------------------|-------------|--|---------|--------------|----------------------------------|------------------------------|
| MODEL NUMBER | PART NUMBER | DESCRIPTION | | MODEL NUMBER | PART NUMBER | DESCRIPTION |
| BOVA-36HDN1-M20G | 8733952437 | 36 kBTU/hr (3 ton), Condensing Unit 2.0 | EHK-05B | | EHK-05B 7739832075 5 kW Electric | |
| BOVA-60HDN1-M20G | 8733952438 | 60 kBTU/hr (5 ton), Condensing Unit 2.0 | | | 7700000070 | |
| BOSCH BVA MODEL AIR HANDLER | | | | EHK-08B | 7739832076 | 7.5 kW Electric Strip heater |
| BVA-24WN1-M20 | 8733952439 | 24 kBTU/hr (2 ton), Air Handler Unit 2.0 | | EHK-10B | 7739832077 | 10 kW Electric Strip heater |
| BVA-36WN1-M20 | 8733952440 | 36 kBTU/hr (3 ton), Air Handler Unit 2.0 | | EHK-15B | 7739832078 | 15 kW Electric Strip heater |
| BVA-48WN1-M20 | 8733952441 | 48 kBTU/hr (4 ton), Air Handler Unit 2.0 | | | | |
| BVA-60WN1-M20 | 8733952442 | 60 kBTU/hr (5 ton), Air Handler Unit 2.0 | | EHK-20B | 7739832079 | 20 kW Electric Strip heater |

| INVERTER DUCTED SPLIT AHRI 210/240 PERFORMANCE DATA | | | | | | | | | |
|---|--------------------|--------------------------|--------------------|---------------------|--------|---------------------|-------|-----------|--|
| OUTDOOR UNIT | INDOOR AIR HANDLER | COOLING CAPACITY (BTU/H) | | | HEATIN | | | | |
| MODEL | MODEL | TOTAL | EER ⁽³⁾ | SEER ⁽⁴⁾ | HI | HSPF ⁽⁵⁾ | LOW | CFM | |
| BOVA-36HDN1-M20G | BVA-24WN1-M20 | 24000 | 14 | 20.5 | 24000 | 10.5 | 23000 | 860/680 | |
| BOVA-36HDN1-M20G | BVA-36WN1-M20 | 34600 | 12.5 | 20 | 34200 | 10.5 | 28000 | 1150/820 | |
| BOVA-60HDN1-M20G | BVA-48WN1-M20 | 47500 | 13.5 | 20 | 48000 | 10.5 | 40000 | 1530/1150 | |
| BOVA-60HDN1-M20G | BVA-60WN1-M20 | 54500 | 12.5 | 19 | 56000 | 10.5 | 44000 | 1750/1350 | |

| INVERTER DUCTED SPLIT + CASED COIL ONLY AHRI 210/240 PERFORMANCE DATA | | | | | | | | | | |
|---|--------------|--------|--------------------------|---------------------|-------|--------------------------|-------|-----------|--|--|
| OUTDOOR UNIT | CASED COIL | COOLIN | COOLING CAPACITY (BTU/H) | | | HEATING CAPACITY (BTU/H) | | | | |
| MODEL | MODEL | TOTAL | EER ⁽³⁾ | SEER ⁽⁴⁾ | HI | HSPF ⁽⁵⁾ | LOW | CFM | | |
| BOVA-36HDN1-M20G | BMAC2430ANTD | 23400 | 11.8 | 16.5 | 23400 | 9.5 | 18000 | 750/600 | | |
| BOVA-36HDN1-M20G | BMAC2430BNTD | 23600 | 11.8 | 16.5 | 23800 | 9.5 | 18000 | 800/600 | | |
| BOVA-36HDN1-M20G | BMAC3036ANTD | 32000 | 10.8 | 16 | 33600 | 9.5 | 22000 | 900/750 | | |
| BOVA-36HDN1-M20G | BMAC3036BNTD | 32400 | 11.2 | 16 | 33800 | 9.5 | 23000 | 1000/800 | | |
| BOVA-36HDN1-M20G | BMAC3036CNTD | 32600 | 11.4 | 16 | 34000 | 9.5 | 23000 | 1050/800 | | |
| BOVA-60HDN1-M20G | BMAC4248BNTF | 43000 | 11.2 | 16.5 | 44500 | 9.5 | 31500 | 1200/1050 | | |
| BOVA-60HDN1-M20G | BMAC4248CNTF | 44000 | 11.8 | 16.5 | 46000 | 9.5 | 32000 | 1350/1050 | | |
| BOVA-60HDN1-M20G | BMAC4248DNTF | 45000 | 11.8 | 16.5 | 46500 | 9.5 | 32000 | 1450/1050 | | |
| BOVA-60HDN1-M20G | BMAC4860CNTF | 55000 | 10.5 | 16 | 55500 | 9.5 | 38000 | 1350/1150 | | |
| BOVA-60HDN1-M20G | BMAC4860CNTF | 56000 | 10.5 | 16 | 56000 | 9.5 | 39000 | 1500/1150 | | |

| INVERTER DUCTED SPLIT + CASED COIL + 96% FURNACE AHRI 210/240 PERFORMANCE DATA | | | | | | | | | | |
|--|------------------|--------------|---------------------|--------------------------|--------------------|---------------------|--------------------------|---------------------|-------|-----------|
| SYSTEM | OUTDOOR UNIT | CASED COIL | PAIRING FURNACES | COOLING CAPACITY (BTU/H) | | | HEATING CAPACITY (BTU/H) | | | CFM |
| TONNAGE | MODEL | MODEL | | TOTAL | EER ⁽³⁾ | SEER ⁽⁴⁾ | ні | HSPF ⁽⁵⁾ | LOW | |
| 2 | BOVA-36HDN1-M20G | BMAC2430ANTD | BGH96M060B3A | 24000 | 13 | 18.5 | 24000 | 10 | 18000 | 820/630 |
| | BOVA-36HDN1-M20G | BMAC2430ANTD | BGH96M080B3A | 24000 | 13 | 18.5 | 24000 | 10 | 18000 | 800/580 |
| 2 | BOVA-36HDN1-M20G | BMAC2430BNTD | BGH96M060B3A | 24000 | 13.5 | 19 | 24000 | 10 | 19000 | 860/680 |
| | BOVA-36HDN1-M20G | BMAC2430BNTD | BGH96M080B3A | 24000 | 13.5 | 19 | 24000 | 10 | 19000 | 840/630 |
| | BOVA-36HDN1-M20G | BMAC3036ANTD | BGH96M060B3A | 32200 | 11.2 | 17 | 34000 | 10 | 25000 | 1050/800 |
| | BOVA-36HDN1-M20G | BMAC3036ANTD | BGH96M080B3A | 32200 | 11.2 | 17 | 34000 | 10 | 25000 | 1020/800 |
| | BOVA-36HDN1-M20G | BMAC3036BNTD | BGH96M060B3A | 33000 | 11.6 | 17.5 | 34200 | 10 | 25000 | 1100/850 |
| 3 | BOVA-36HDN1-M20G | BMAC3036BNTD | BGH96M080B3A | 33000 | 11.6 | 17.5 | 34200 | 10 | 25000 | 1070/850 |
| 3 | BOVA-36HDN1-M20G | BMAC3036CNTD | BGH96M080C4A | 33600 | 12 | 18 | 34200 | 10 | 25000 | 1050/820 |
| | BOVA-36HDN1-M20G | BMAC3036CNTD | BGH96M100C5A | 33600 | 12 | 18 | 34200 | 10 | 25000 | 1150/750 |
| | BOVA-36HDN1-M20G | BMAC4248BNTF | BGH96M080B3A | 33000 | 12.5 | 18.5 | 34200 | 10 | 26000 | 1000/850 |
| | BOVA-36HDN1-M20G | BMAC4248CNTF | BGH96M100C5A | 33000 | 12.5 | 18.5 | 34200 | 10 | 26000 | 1100/800 |
| | BOVA-60HDN1-M20G | BMAC4248BNTF | BGH96M080B3A | 43000 | 11.2 | 18 | 45000 | 9.5 | 34000 | 1250/1050 |
| | BOVA-60HDN1-M20G | BMAC4248CNTF | BGH96M080C4A | 44000 | 12 | 18.5 | 46000 | 10 | 35000 | 1250/1050 |
| 4 | BOVA-60HDN1-M20G | BMAC4248CNTF | BGH96M100C5A | 45000 | 12.5 | 18.5 | 46500 | 10 | 35000 | 1450/1150 |
| | BOVA-60HDN1-M20G | BMAC4248DNTF | BGH96M100D5A | 45500 | 12.5 | 18.5 | 47000 | 10 | 35000 | 1500/1200 |
| | BOVA-60HDN1-M20G | BMAC4248DNTF | BGH96M120D5A | 45500 | 12.5 | 18.5 | 47000 | 10 | 35000 | 1500/1200 |
| | BOVA-60HDN1-M20G | BMAC4860CNTF | BGH96M100C5A | 52000 | 12 | 18 | 53500 | 10 | 37000 | 1450/1150 |
| 5 | BOVA-60HDN1-M20G | BMAC4860DNTF | BGH96M100D5A | 52000 | 12.5 | 18.5 | 54000 | 10 | 38000 | 1500/1200 |
| | BOVA-60HDN1-M20G | BMAC4860DNTF | BGH96M120D5A | 52000 | 12.5 | 18.5 | 54000 | 10 | 38000 | 1500/1200 |

Blue Text = ENERGY STAR Certified. (3) Energy Efficiency Ratio; Certified per AHRI 210/240. (4) Seasonal Energy Efficiency Ratio; Certified per AHRI 210/240. (5) HSPF = Heating Seasonal Performance Factor; Certified per AHRI 210/240. Note: Always check the rating plate for electrical data on the unit being installed. The listed data is for reference only. Please consult boschheatingandcooling.com for further details.

About **Bosch**

Bosch Group

The Bosch Group is a leading global supplier of technology and services in the areas of Automotive, Industrial Technology, Consumer Goods and Building Technology. The company was founded in Stuttgart, Germany, in 1886 and presently has more than 440 subsidiaries and is represented in over 150 countries.

In the U.S., Canada and Mexico, the Bosch Group manufactures and markets automotive original equipment and aftermarket solutions, industrial drives and control technology, power tools, security and communication systems, packaging technology, thermotechnology, household appliances and software solutions. The Bosch Group's products and services are designed to improving quality of life by providing innovative and beneficial solutions. In this way, the company offers technology worldwide that is "Invented for life." Additional information is available online at boschheatingandcooling.com and bosch.ca.

Bosch Thermotechnology in North America

Bosch Thermotechnology is a leading source of high quality water heating and comfort systems. The company offers gas tankless, electric whole house and point-of-use water heaters, Bosch and Buderus floor-standing and wall mounted boilers, Bosch and FHP geothermal, water-source and air-source systems as well as controls and accessories for all product lines. Bosch Thermotechnology is committed to being Simply Smart by offering products that work together as integrated systems that enhance quality of life in an ultra-efficient and environmentally friendly manner. For more information, visit boschheatingandcooling.com.

Bosch Water-Source Heat Pumps: Made in the U.S.A.

Bosch and FHP water-source and geothermal heat pumps are made by highly trained and skilled workers in our factory based in Fort Lauderdale, Florida. They are manufactured with rigorous standards and factory testing ensuring high efficient operation over the life of the unit. Bosch's ISO 9001 and ISO 14001 certified facilities provide consistent quality in every unit built.



www.BoschHeatingAndCooling.com

Bosch Thermotechnology Corp. Watertown, MA • Londonderry, NH • Ft. Lauderdale, FL General Inquiries: 1-866-642-3198

Copyright © 2019 Bosch Thermotechnology Corp. All rights reserved. Subject to change without notice.